

### Damp area distribution box E1310 EU



#### Available Colours

E1310ws EU / white	7340462
E1310gr EU / grey	7340484
E1310sw EU / black	7340487
E1310gn EU / green	7340486
E1310rt EU / red	7340485

#### Easy to use - Stable execution

- Easy to install
- Easy to use - no need for expensive, additional tools
- With integrated push-out membranes on all four sides
- With back side membrane introduction for cables of up to 5x2,5mm<sup>2</sup>
- Can be equipped with strain relief ABZK-ZE

#### Dimensions

Depth	37 mm
Length	85 mm
Width	85 mm

#### Environmental conditions

Ambient temperature (24h)	35 °C
Ambient temperature (maximum)	40 °C
Ambient temperature (minimum)	-25 °C
Max. rel. humidity at 25°C (short term)	90 %
Max. rel. humidity at 40°C	50 %

#### Material

Housing material	PP/TPE
Lid material	PE

### Properties

Degree of protection (IP)	IP65
Halogen-free	true
Installation type	SM
Insulation	Protection class II
Silicone-free	true

### Technical features

Cable entry 7x1,5 <sup>2</sup> /5x2,5 <sup>2</sup>	12
Design voltage	500 V
Ground inserts	2
max. cross section	2,5 mm <sup>2</sup>

### Certificates & standards

CE	true
Glow wire test	650 °C
REACH	true
RoHS	true
Standards	<ul style="list-style-type: none"><li>• DIN EN 60670-1 (VDE 0606-1)</li><li>• DIN EN 60670-22 (VDE 0606-22)</li></ul>
VDE	true

### Accessories

Equipped with	None
Recommended purchase	ABZK-ZE / 7390153

