



**\*Discontinued product\* HW/FM Small distributor  
JUMBO with support frame**

Order number: 7250025

Type: JUMBO36+6XX

**Preassemblable with System**

- Optionally, can be used for flush mounting or hollow wall mounting
- Generous wiring space
- Strain relief possible
- Packaging can be used as plaster protection
- Suitable with HWA-Set for hollow wall installation

suitable for:

**Dimensions**

Depth	98 mm
Height	650 mm
Height of HW cut-out	610 mm
Height of mounting recess	643 mm
Plaster compensation	15 mm
Width	365 mm
Width of HW cut-out	323 mm
Width of mounting recess	359 mm

**Material**

Box material	PS
Cover material	PS
Door material	

**Environmental conditions**

Ambient temperature (24h)	35 °C
Ambient temperature (maximum)	40 °C
Ambient temperature (minimum)	-25 °C
Max. rel. humidity at 25°C (short term)	95 %
Max. rel. humidity at 40°C	50 %

### Properties

Can be lead sealed	true
Colour	White
Degree of protection (IP)	IP30
Free of heavy metals	true
Halogen-free	-
Installation type	
Insulation	protection class II
Number of compartments	42
Number of rows	3
PVC-free	true
Silicone-free	true
Stackable	true
Weather-resistant	-

### Technical features

Design current	63 A
Design voltage	400 V
Permissible power loss according to DIN 43 873	
Suitable for sheet thickness	10-45 mm

### Certificates & standards

CE	true
Glow wire test	850 °C
REACH	true
RoHS	true
Standards	<ul style="list-style-type: none"><li>• DIN EN 60670-1</li><li>• DIN EN 60670-24</li><li>• DIN EN 61439-1</li><li>• DIN EN 61439-3</li><li>• DIN 43871</li></ul>
VDE	true

### Accessories

Equipped with	1x door with frame (T+RJUMBO36+6) 1x PE screw terminal (KPE34) 1x N-N screw terminal (KN17N)
Recommended purchase	Hollow wall anchor set (HWA-Set) Wall claw set (MK-Set) Mounting bracket set (MH-Set) Cover strip (ADS12W)