



Damp area distribution box IP65, 80x80x63mm

Order number: 7340061

Type: FK111

For stringent requirements and severe operating conditions

- High resistance to breakage
- With pre-punched cable entries
- With double membrane seals (IP54)
- Lid with stainless steel screws
- Lid with stainless steel screws
- Insulating and sealing plugs enclosed

Dimensions

Depth	63 mm
Length	80 mm
Width	80 mm

Environmental conditions

Ambient temperature (24h)	35 °C
Ambient temperature (maximum)	40 °C
Ambient temperature (minimum)	-25 °C
Max. rel. humidity at 25°C (short term)	90 %
Max. rel. humidity at 40°C	50 %

Material

Box material	PS
Lid material	PS

Properties

Can be lead sealed	-
Colour	White
Degree of protection (IP)	IP65
Free of heavy metals	true
Halogen-free	true
Installation type	SM
PVC-free	true
Silicone-free	true
Stackable	-
Weather-resistant	-

Technical features

Design voltage	400 V
max. cross section	4 mm ²
Pipe entry M20	7

Certificates & standards

CE	true
Glow wire test	650 °C
REACH	true
RoHS	true
Standards	<ul style="list-style-type: none"> DIN EN 60670-1 (VDE 0606-1) DIN EN 60670-22 (VDE 0606-22)
VDE	true

Accessories

Equipped with	None
---------------	------