



**Damp area distribution box IP65, 140x140x79mm**

Order number: 7340066

Type: FK310

For stringent requirements and severe operating conditions

- High resistance to breakage
- With pre-punched cable entries
- With double membrane seals (IP54)
- Lid with stainless steel screws
- Lid with stainless steel screws
- Insulating and sealing plugs enclosed

**Dimensions**

Depth	79 mm
Length	140 mm
Width	140 mm

**Environmental conditions**

Ambient temperature (24h)	35 °C
Ambient temperature (maximum)	40 °C
Ambient temperature (minimum)	-25 °C
Max. rel. humidity at 25°C (short term)	90 %
Max. rel. humidity at 40°C	50 %

**Material**

Box material	PS
Lid material	PS

### Properties

Can be lead sealed	-
Colour	grey
Degree of protection (IP)	IP65
Free of heavy metals	true
Halogen-free	true
Installation type	SM
PVC-free	true
Silicone-free	true
Stackable	-
Weather-resistant	-

### Technical features

Design voltage	400 V
max. cross section	16 mm²
Pipe entry M20	2
Pipe entry M20/M25	5
Pipe entry M25/M32	5

### Certificates & standards

CE	true
Glow wire test	650 °C
REACH	true
RoHS	true
VDE	-